



Highlights

2 to 24 poles

Vertical pin strip

Spacing 5.08 mm

Open ends

Wire Sizes

Solid min -

Solid max -

Stranded (flexible) min -

Stranded (flexible) max -

Stranded with ferrule min -

Stranded with ferrule max -

Dimensions

PCB hole diameter 1.4 mm

Materials

Contact pin Copper Alloy

Insulating Material

Material PA 6.6

Flammability class UL 94 V-0

Temperatures

Operating temperature -40 °C (without mech. load) - 105 °C

Store temperature -40 °C - 105 °C

Wave Soldering Process

Soldering temperature, recommended 260 °C

Peak soldering time, recommended 3-4 s

Reflow Process

Soldering temperature, recommended -

Peak soldering time, recommended -



Technical Data // STLZ950/..-5.08-V-GREEN

Spacing 5.08 mm

Colours

GREEN, RAL 6018

BLACK, RAL 9011



BASALT GREY, RAL 7012

LIGHT GREY, RAL 7035

LIGHT GREEN, similar RAL 6018

Colours according to RAL, there may be variations on colour due to production conditions.
Special colours on request.

Ratings

UseGroup	c  US			
	B	C	D	
Rated voltage	300 V	150 V	300 V	250 V
Rated current	15 A	15 A	10 A	12 A
Overvoltage category				III
Test voltage	1.60 kV	1.30 kV	1.60 kV	4.0 kV
Pollution degree				3




Counterparts (Spacing 5.08 mm)

Pin Strip/Terminal Block

STLZ950-INV	AKZ950	AKZ955	AKZ1100	AKZ1110	AKZ1200	AKZ4951
-------------	--------	--------	---------	---------	---------	---------

In combination of connectors with different admission data, the lower value is valid.

Accessoires

Figure	Designation	Article Number
	Coding Star CS3-5.0/5.08-RED 2-6 poles	Order data: 50000000025
	Coding Star CS2-5.0/5.08-RED 7-24 poles	Order data: 50000000024
	Separating Element SE-STL950-GREEN	Order data: 50950000002

**Technical Data // STLZ950/..-5.08-V-GREEN**

Spacing 5.08 mm

Order Data (Spacing 5.08 mm)

Number of Poles	Width (mm)	Article Designation	Article Number	PU
2	10.16	STLZ950/2-5.08-V-GREEN	50950025131 F	200
3	15.24	STLZ950/3-5.08-V-GREEN	50950035131 F	200
4	20.32	STLZ950/4-5.08-V-GREEN	50950045131 F	200
5	25.40	STLZ950/5-5.08-V-GREEN	50950055131 E	100
6	30.48	STLZ950/6-5.08-V-GREEN	50950065131 E	100
7	35.56	STLZ950/7-5.08-V-GREEN	50950075131 E	100
8	40.64	STLZ950/8-5.08-V-GREEN	50950085131 D	50
9	45.72	STLZ950/9-5.08-V-GREEN	50950095131 D	50
10	50.80	STLZ950/10-5.08-V-GREEN	50950105131 D	50
11	55.88	STLZ950/11-5.08-V-GREEN	50950115131 D	50
12	60.96	STLZ950/12-5.08-V-GREEN	50950125131 D	50
13	66.04	STLZ950/13-5.08-V-GREEN	50950135131 D	50
14	71.12	STLZ950/14-5.08-V-GREEN	50950145131 D	50
15	76.20	STLZ950/15-5.08-V-GREEN	50950155131 D	50
16	81.28	STLZ950/16-5.08-V-GREEN	50950165131 D	50
17	86.36	STLZ950/17-5.08-V-GREEN	50950175131 D	50
18	91.44	STLZ950/18-5.08-V-GREEN	50950185131 D	50
19	96.52	STLZ950/19-5.08-V-GREEN	50950195131 D	50
20	101.60	STLZ950/20-5.08-V-GREEN	50950205131 D	50
21	106.68	STLZ950/21-5.08-V-GREEN	50950215131 D	50
22	111.76	STLZ950/22-5.08-V-GREEN	50950225131 D	50
23	116.84	STLZ950/23-5.08-V-GREEN	50950235131 D	50
24	121.92	STLZ950/24-5.08-V-GREEN	50950245131 D	50



Technical Data // **STLZ950/..-5.08-V-GREEN**

Spacing 5.08 mm

Technical drawing

